



Your Quality Source for Electrical Wire

U.L. AWM Style 1199

AWG	# OF STR.	AWG OF STR.	NOM. DIA. OF STR. COND.	NOM. FIN. WIRE DIAM.	MAX. RES. (DC AT 20C) OHM/PER 1K FEET	NOM. WT.
30	1	30	.0100	.0494	110	2.15
28	1	28	.0126	.0520	69.3	2.50
26	19	38	.0197	.0591	45.8	3.34
26	7	34	.0197	.0591	45.8	3.30
26	1	26	.0157	.0551	43.5	2.97
24	19	36	.0240	.0643	28.7	4.25
24	7	32	.0240	.0634	28.7	4.05
24	1	24	.0201	.0594	27.3	3.72
22	19	35	.0299	.0693	18.1	5.11
22	7	30	.0299	.0693	18.1	5.42
22	1	22	.0252	.0646	17.2	4.73
20	19	33	.0374	.0768	11.2	6.81
20	7	29	.0362	.0756	11.2	6.48
20	1	20	.0320	.0714	10.7	6.37
18	19	31	.0465	.0858	7.06	9.11
18	7	26	.0465	.0858	7.06	9.18
18	1	18	.0402	.0795	6.77	8.67
16	26	30	.0591	.0984	4.45	12.87
16	19	29	.0591	.0984	4.45	13.02
16	1	16	.0512	.0906	4.26	12.45
14	41	30	.0740	.1134	2.73	18.41
14	19	27	.0740	.1134	2.73	18.48
12	65	30	.0933	.1327	1.72	26.99
12	19	25	.0992	.1386	1.72	29.99
10	105	30	.1181	.1575	1.08	40.80
10	19	23	.1209	.1602	1.08	42.39

UL 1199
 Extruded PTFE
 Electronic Hook Up Wire
 UL & CSA Approved
 600V
 200 Celsius

UL 1199 is ideal for general appliance wiring and where chemical exposure, temperature extremes, and dielectric stresses are possible. They provide exceptional savings in both weight and space.

