



Your Quality Source for Electrical Wire

U.L. AWM Style 1284

AWG	CONUDCTOR MATERIAL	NO. OF STRANDS	AWG OF STRANDS	WIRE O.D.	APPROX WEIGHT LBS/1K FEET
1	BC	133	22	0.535	324
1	TC	259	25	0.521	324
1	BC	833	30	0.521	332
1	TC	833	30	0.521	332
1/0	BC	259	24	0.561	401
1/0	TC	259	24	0.561	401
1/0	BC	1064	30	0.561	402
1/0	TC	1064	30	0.561	402
2/0	BC	259	23	0.625	485
2/0	TC	258	23	0.660	495
2/0	BC	1330	30	0.616	492
2/0	TC	1330	30	0.616	495
3/0	BC	259	22	0.666	610
3/0	TC	259	22	0.666	601
3/0	BC	1672	30	0.666	612
3/0	TC	1672	30	0.666	612
4/0	BC	259	21	0.735	800
4/0	TC	551	24	0.740	773
4/0	BC	2109	30	0.726	758
4/0	TC	2109	30	0.726	758
250	TC	2451	30	.835	978
250	BC	2451	30	.835	978
350	BC	3458	30	1.045	1350

U.L. AWM Style 1284

PVC

Stranded conductors

Applications: Control cabinets, internal wiring of appliances and machine tools.

Conductor: Tinned or bare copper

Temperature: -40 to 105 Celsius

Voltage: 600 Volts

