



Your Quality Source for Electrical Wire

U.L. AWM Style 1371

AWG	COND. STRANDING	NOM. INSUL. THICK. (IN)	NOM. O.D. (IN)	APPROX LBS/MTF
32	7/40	0.006	0.0220	1
30	7/38	0.006	0.0240	1
28	7/36	0.006	0.0270	1
26	7/34	0.006	0.0310	2
24	7/32	0.006	0.0360	2
24	19/36	0.006	0.0360	2
22	7/30	0.006	0.0420	4
22	19/34	0.006	0.0420	4

Belden Mil-W-16878/6 (Type ET) Hook-Up Wire

UL 1371

Belden M16878/6 (Type ET), UL 1371 Hook-Up Wire Ratings and Approvals:

Military Specification: Mil-DTL-16878 (200°C)

NEMA: Type ET

UL Approval: UL AWM Style 1371 (105°C)

Voltage Rating: 250V

Flame Test: VW-1

Belden M16878/6 (Type ET), UL 1371 Hook-Up Wire Construction:

Conductor: Stranded Silver-Plated Copper

Insulation: Extruded Teflon

Belden M16878/6 (Type ET), UL 1371 Hook-Up Wire Additional Information:

Belden's UL 1371 & Mil-W-16878/6 carry specific temperature approvals based on whether the UL standard is needed versus the Mil-Spec standard. See specific part for full spec information and approvals.

