



Your Quality Source for Electrical Wire

U.L. AWM Style 3239

AWG	COND. STRANDING	NOM. INSUL. THICK. (IN)	NOM. O.D. (IN)	APPROX LBS/MFT
24	7/30	0.040	0.0990	7.00
24	7/30	0.050	0.1170	7.00
24	7/32	0.062	0.1480	10.00
24	7/32	0.097	0.2180	20.00
22	7/30	0.031	0.2150	9.80
22	7/30	0.035	0.1090	7.00
22	19/34	0.040	0.1090	7.00
22	7/30	0.045	0.1150	7.00
22	19/34	0.050	0.1230	10.00
22	7/30	0.045	0.1230	9.00
22	7/30	0.062	0.1490	11.00
22	7/30	0.097	0.2240	21.00
20	7/28	0.040	0.1250	12.00
20	7/28	0.045	0.1280	9.00
20	10/30	0.050	0.1300	10.00
20	7/28	0.050	0.1380	10.00
20	19/32	0.050	0.1300	10.00
20	7/28	0.062	0.1620	13.00
20	7/28	0.097	0.2320	25.00
18	16/30	0.040	0.1220	12.00
18	16/30	0.045	0.1350	12.00
18	16/30	0.050	0.1410	13.00
18	16/30	0.062	0.1690	16.00
18	16/30	0.097	0.2490	27.00
16	26/30	0.040	0.1370	16.00
16	26/30	0.045	0.1480	16.00
16	26/30	0.050	0.1550	17.00
16	26/30	0.062	0.1820	20.00
16	26/30	0.097	0.2520	32.00
14	41/30	0.040	0.1500	22.00
14	41/30	0.045	0.1640	22.00
14	41/30	0.050	0.1680	23.00
14	41/30	0.062	0.1980	27.00
14	41/30	0.097	0.2680	40.00
12	65/30	0.040	0.1700	31.00
12	65/30	0.045	0.1810	30.00

12	65/30	0.050	0.1880	32.00
12	65/30	0.062	0.2150	36.00
12	65/30	0.097	0.2850	50.00
10	65/28	0.040	0.1950	44.00
10	65/28	0.050	0.2150	46.00
10	105/30	0.045	0.2140	48.00
10	105/30	0.062	0.2480	50.00
10	105/30	0.097	0.3180	66.00
8	133/29	0.1660	0.260	54.00
8	133/29	0.068	0.3010	80.00
8	133/29	0.097	0.3810	120.00
6	133/27	0.068	0.3810	120.00
4	133/25	0.068	0.4010	166.00
2	259/26	0.068	0.4650	259.00

U.L. AWM Style 3239

High Voltage Lead Wire, HVSR

150°C Silicone Rubber/PVC

UL 3239 High Voltage Lead Wire Description:

Conductors: Fully annealed tinned copper, flexible stranding

Insulation: High temperature, high voltage silicone rubber (HVSR) - easy stripping

High dielectric strength

Flame retardant

UL 3239 High Voltage Lead Wire Applications:

HVSR lead wire may be used in TV receivers, stoves, heaters, furnaces, dryers, signs, lighting fixtures, and high temperature electronic devices.

