



Your Quality Source for Electrical Wire

U.L. AWM Style 3271

AWG	COND. STANDING	NOM. INSUL. THICK. (IN)	NOM. O.D. (IN)	APPROX LBS/MFT
26	7/34	0.031	0.0810	3.80
24	Solid	0.031	0.0830	4.40
24	7/32	0.031	0.0870	4.40
22	Solid	0.031	0.0880	5.40
22	7/30	0.031	0.0920	6.00
20	Solid	0.031	0.0950	6.90
20	10/30	0.031	0.1010	7.00
18	7/28	0.031	0.1010	7.30
18	16/30	0.031	0.1090	9.00
16	19/29	0.031	0.1200	13.10
16	26/30	0.031	0.1220	14.00
14	41/30	0.031	0.1370	19.00
14	19/27	0.031	0.1340	19.10
12	65/30	0.031	0.1560	28.00
12	19/25	0.031	0.1540	0.00
10	105/30	0.031	0.1820	43.00
10	37/26	0.031	0.1790	41.80
8	133/29	0.047	0.2630	74.00
6	133/27	0.65	0.3390	121.00
4	133/25	0.065	0.3950	180.00
2	655/30	0.065	0.4530	267.00
1	817/30	0.085	0.5500	347.00
1/0	1045/30	0.085	0.5830	425.00
2/0	1330/30	0.085	0.6450	530.00
3/0	1672/30	0.085	0.7050	651.00
4/0	2109/30	0.085	0.7600	811.00

U.L. AWM Style 3271

Irradiated Cross-linked Polyethylene

Electronic Hook Up Wire

UL Recognized & CSA Certified

125°C, 600V

Conductor: UL 3271 possesses a soft annealed, solid or stranded, tinned copper conductor

Insulation: Irradiation Cross-Linked Polyethylene Insulation (XLPE)

UL 3271 Applications: UL 3271 Hook Up Wire may be used for internal wiring of appliances, computers, test equipment, business machines and other office and control equipment.

