



**Product:** [8205](#)

Electronic, 2 C #20 Str TC, PVC Ins, PVC Jkt, CMG

[Request Sample](#)

**Product Description**

Electronic, 2 Conductor 20AWG (7x28) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

**Technical Specifications**

**Product Overview**

Suitable Applications:	low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring
------------------------	---

**Construction Details**

**Conductor**

Element	Number of Element	Size	Stranding	Material
Pair(s)	1	20 AWG	7x28	TC - Tinned Copper

**Insulation**

Element	Material	Nom. Thickness	Color Code
Pair(s)	PVC - Polyvinyl Chloride	0.015 in (0.38 mm)	Black & Red

**Outer Jacket**

Material	Nom. Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.025 in (0.64 mm)	0.180 in (4.57 mm)

Cable Diameter (Nominal):	0.180 in (4.57 mm)
---------------------------	--------------------

**Electrical Characteristics**

**Electricals**

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Pair(s)	10 Ohm/1000ft (33 Ohm/km)	24.5 pF/ft (80.4 pF/m)	3.7 Amps per Conductor at 20°C

**Voltage**

UL Voltage Rating
300 V (CMG)

**Mechanical Characteristics**

**Temperature**

UL Temperature	Operating
-20°C to +60°C	-20°C to +60°C

**Bend Radius**

Stationary Min.	Installation Min.
1.8 in (46 mm)	1.8 in (46 mm)

Max. Pull Tension:	28 lbs (13 kg)
Bulk Cable Weight:	16 lbs/1000ft (24 kg/km)

**Standards and Compliance**

Environmental Suitability:	Indoor
Sustainability:	CA Prop 65
Flammability / Fire Resistance:	UL1685 FT4 Loading, FT4, IEC 60332-1-2
NEC / UL Compliance:	Article 800, CMG
CEC / C(UL) Compliance:	CMG
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

## History

Update and Revision:	Revision Number: 0.349 Revision Date: 10-13-2021
----------------------	--

## Variants

Item #	Color	Putup Type	Length	UPC/EAN
8205.0030	Chrome	Reel	30 m	8719605018076
8205.00U152	Chrome	UnReel	152 m	8719605018083
8205.01152	Chrome	Reel	152 m	8719605018106
8205.00U305	Chrome	UnReel	305 m	8719605018090
8205.01305	Chrome	Reel	305 m	8719605018113
8205 060U500	Chrome	UnReel	500 ft	612825195986
8205 0601000	Chrome	Reel	1,000 ft	612825196006
8205 0605000	Chrome	Reel	5,000 ft	612825196020

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.