



Your Quality Source for Electrical Wire

BOAT Cable

AWG	NO. OF COND.	COND. STR.	NOM. INSUL. THICK. (IN)	APPROX DIMENSION	JACKET THICK.	APPROX LBS/MFT
18	2	16/30	0.032	.17 x .280	0.030	33.00
16	2	26/30	0.032	.18 x .322	0.030	42.00
16	3	26/30	0.032	.18 x .448	0.030	59.00
14	2	41/30	0.032	.20 x .356	0.030	55.00
14	3	41/30	0.032	.20 x .499	0.030	77.00
12	2	65/30	0.032	.21 x .392	0.030	73.00
12	3	65/30	0.030	.21 x .556	0.032	54.00
10	2	105/30	0.032	.24 x .450	0.030	102.00
10	3	105/30	0.032	.24 x .640	0.030	150.00
8	2	133/29	0.048	.33 x .608	0.030	190.00

Flat Multi-Conductor Marine Cable

Boat Cable

Polyvinylchloride (PVC)

105°C Dry/75°C Wet; 600 Volts

Marine Cable Features:

Flat boat cable can be used for marine and brake cable.

Meets UL Style BC-5W2 for boat cable. (UL 1426 rating available upon request)

Flat Boat Cable Construction:

Conductor: Stranded Tinned Copper

Jacket: Polyvinylchloride (PVC), White or Gray

Insulation: Polyvinylchloride (PVC)

Standard Color Code: 1: Black, 2: White, 3: Green