



Your Quality Source for Electrical Wire

**Flat Festoon Cable**

| AWG       | NUMBER OF CONDUCTORS | CONDUCTOR STR | AWG OF STR. | INSULATION THICKNESS | AMPACITY | DIMENSIONAL DATA | NOM. WT LBS PER 1K FEET |
|-----------|----------------------|---------------|-------------|----------------------|----------|------------------|-------------------------|
| <b>16</b> | 4                    | 65            | 34          | 0.015                | 18       | 0.19 x 0.0485"   | 94                      |
| <b>16</b> | 8                    | 65            | 34          | 0.015                | 12       | 0.19 x 0.87      | 130                     |
| <b>16</b> | 12                   | 65            | 34          | 0.015                | 9        | 0.19 x 1.255     | 198                     |
| <b>14</b> | 8                    | 105           | 34          | 0.015                | 17       | 0.204 x 0.982    | 206                     |
| <b>14</b> | 12                   | 105           | 34          | 0.015                | 12       | 0.204 x 1.423    | 287                     |
| <b>12</b> | 4                    | 105           | 30          | 0.015                | 30       | 0.22 x 0.60      | 112                     |
| <b>10</b> | 4                    | 105           | 30          | 0.018                | 40       | 0.246 x 0.709    | 210                     |
| <b>6</b>  | 4                    | 266           | 30          | 0.022                | 75       | 0.350 x 1.13     | 462                     |

UL/CSA Portable Cord  
 600 Volts  
 -40 to 105 Celsius  
 Finely stranded tinned conductor  
 Fluoropolymer insulation  
 Abrasion, Chemicals, and Flexing

