



Your Quality Source for Electrical Wire

**Flat Submersible cable**

AWG	NUMBER OF CONDUCTORS	NUM. OF GROUND	CONDUCTOR STR	DIMENSIONS INSULATION (IN.)	DIMENSIONS JACKET (IN.)	DIMENSIONS (IN.)	AMPACITY	WEIGHT (LB./1K FEET)
14	2	14/1	7	0.045	0.045	0.25 x 0.58	15	114
12	2	12/1	19	0.045	0.045	0.27 x 0.64	20	154
10	2	10/1	19	0.045	0.045	0.30 x 0.71	30	212
8	2	10/1	19	0.060	0.045	0.35 x 0.82	50	278
14	3	14/1	7	0.045	0.045	0.25 x 0.74	15	147
12	3	12/1	19	0.045	0.045	0.27 x 0.82	20	192
10	3	10/1	19	0.045	0.045	0.30 x 0.91	30	258
8	3	10/1	19	0.060	0.045	0.35 x 1.08	50	376
6	3	8/1	19	0.060	0.045	0.39 x 1.26	65	258
4	3	8/1	19	0.060	0.045	0.44 x 1.40	85	726
2	3	6/1	19	0.060	0.045	0.49 x 1.60	115	1,049

UL 83

75 Celsius Wet/Dry

600 Volts

Stranded copper conductors, insulated with color coded PVC (type THW), configured flat and parallel with green insulated ground, and overall PVC jacket applied directly over the conductors with a non-penetrating web.

Suitable for use within the well casing to supply power to the submersible pump and where extra mechanical protection and flexible during installation and operation are required.

