



Your Quality Source for Electrical Wire

U.L. AWM Style 3191 (Hypalon)

AWG	NUMBER OF STR.	AWG OF STR.	INSULATION THICKNESS (IN.)	NOM. FIN. WIRE DIAM. (IN.)	NOM. WT LBS PER 100 FEET
18	16	30	.045	.142	2.3
16	26	30	.045	.155	2.8
14	41	30	.045	.170	3.7
12	65	30	.045	.190	4.6

U.L. AWM Style 3191 (Hypalon)

AWG	NUMBER OF STR.	AWG OF STR.	INSULATION THICKNESS (IN.)	NOM. FIN. WIRE DIAM. (IN.)	NOM. WT LBS PER 100 FEET
10	65	28	.045	.209	6.0

U.L. AWM Style 3192 (Hypalon)

AWG	NUMBER OF STR.	AWG OF STR.	INSULATION THICKNESS (IN.)	NOM. FIN. WIRE DIAM. (IN.)	NOM. WT LBS PER 100 FEET
8	84	27	.045	.209	9.4
6	84	25	.060	.290	13.7
4	105	24	.060	.399	19.1
3	133	24	.060	.420	23.6
2	163	24	.060	.454	30.3

U.L. AWM Style 3193 (Hypalon)

AWG	NUMBER OF STR.	AWG OF STR.	INSULATION THICKNESS (IN.)	NOM. FIN. WIRE DIAM. (IN.)	NOM. WT LBS PER 100 FEET
1	210	24	.080	.557	43.0
1/0	262	24	.080	.607	48.9
2/0	504	26	.080	.668	57.9
3/0	630	26	.080	.732	77
4/0	805	26	.080	.819	95

U.L. AWM Style 3191
600 Volts, 105 Celsius
(CSA Type CL 1053)

U.L. AWM Style 3191, 3192, 3193
600 Volts, 105 Celsius
(CSA Type CL 1052, 300 Volts)

