



Your Quality Source for Electrical Wire

**Military 27500**

AWG	NUMBER OF STR.	AWG OF STR.	PRIMARY DIAMETER (IN.)	SHIELD DIAMETER (IN)	CABLE DIAMETER (IN)	WEIGHT LBS/ 1K FT
24	19	36	.036	.052	.068	6
24	19	36	.036	.088	.094	9
24	19	36	.036	.094	.109	12
24	19	36	.036	.103	.121	15
22	19	34	.043	.059	.075	7
22	19	34	.043	.102	.118	12
22	19	34	.043	.109	.125	17
22	19	34	.043	.120	.136	20
20	19	32	.051	.036	.073	9
20	19	32	.051	.118	.134	18
20	19	32	.051	.133	.144	22
20	19	32	.051	.139	.155	27
18	19	30	.061	.077	.092	12
18	19	30	.061	.138	.154	23
18	19	30	.061	.147	.164	31
18	19	30	.061	.163	.187	40
16	19	29	.070	.086	.092	15
16	19	29	.070	.158	.179	28
16	19	29	.070	.167	.190	39
16	19	29	.070	.185	.209	72
14	19	27	.085	.101	.117	21
14	19	27	.085	.186	.211	40
14	19	27	.085	.199	.223	56
14	19	27	.085	.221	.245	72
12	19	25	.107	.123	.139	30
12	19	25	.107	.230	.252	59
12	19	25	.107	.247	.265	83
12	19	25	.107	.278	.302	111

Stranded tin plated copper conductor  
 Extruded ETFE  
 Tin plated copper braid 85% coverage  
 White extruded ETFE jacket  
 Primary conductors manufactured in accordance to SAE-AS 22759  
 150 Celsius  
 600 Volts