



Your Quality Source for Electrical Wire

NEMA HP-4 KK / MIL-W-16878/12

AWG	NUMBER OF STR.	AWG OF STR.	NOM. DIA. OF STR. COND. (IN.)	NOM. FIN. WIRE DIAM. (IN.)	MAX. RES. (DC AT 20C) OHM/PER 1K FEET	NOM. WT LBS PER 1K FEET
32	1	32	.0089	.037	169.00	1.50
32	7	40	.0100	.039	173.00	1.50
30	1	30	.0100	.040	108.00	1.70
30	7	38	.0120	.042	100.70	1.80
28	1	28	.0126	.043	68.00	2.10
28	7	36	.0150	.045	63.80	2.20
26	1	26	.0159	.046	42.70	2.50
26	7	34	.0190	.049	40.50	2.70
26	19	38	.0200	.049	38.40	2.80
24	1	24	.0201	.050	26.80	3.30
24	7	32	.0240	.054	25.20	3.50
24	19	36	.0250	.054	24.30	3.60
22	1	22	.0254	.056	17.00	4.20
22	7	30	.0300	.060	15.90	4.60
22	19	34	.0320	.060	15.100	4.70
20	1	20	.320	.062	10.50	5.80
20	7	28	.0380	.068	10.00	6.30
20	19	32	.0400	.068	9.190	6.60
18	1	18	.0403	.072	6.60	8.00
18	7	26	.0480	.079	6.280	9.10
18	19	30	.0500	.079	5.790	9.50
16	1	16	.0508	.083	4.200	11.90
16	19	29	.0570	.089	4.520	12.10
14	1	14	.0641	.098	2.580	17.00
14	19	27	.0720	.016	2.880	17.90
12	19	25	.0910	.125	1.810	26.30
10	37	26	.110	.145	1.190	37.80

NEMA HP-4 Type KK | MIL-W-16878/12
 Electronic Hookup Wire
 Extruded FEP Teflon Insulation
 Nominal .015" Wall
 -65 to 200 Celsius
 1000 Volts