



Your Quality Source for Electrical Wire

Round Trailer Cable

AWG	NUMBER OF CONDUCTORS	CONDUCTOR COLORS	CONDUCTOR STRANDING	NOMINAL INSULATION	JACKET THICKNESS	NOMINAL DIAMETER	APPRX LBS./MFT.
16	4	Black, white, brown, red	19/29	.023	.030	.375	120
16	4	Red, Green, Brown, Yellow	19/29	.023	.030	.375	120
16	6	Black, White, Brown, Green, Red, Yellow	19/29	.023	.030	.440	150
16	6	Black, Red, Brown, Green, Blue, Yellow	19/29	.023	.030	.440	150
14	4	Black, White, Brown, Red	19/27	.023	.045	.420	150
14	4	Red, Green, Brown, Yellow	19/27	.023	.045	.420	150
14	6	Black, White, Brown, Green, Red, Yellow	19/27	.023	.060	.490	190
14	6	Black, Red, Brown, Green, Blue, Yellow	19/27	.023	.060	.490	190
14	7	Black, White, Brown, Green, Red, Yellow, Blue	19/27	.023	.060	.535	220
14	4	Brown, Yellow, Green, Red	19/27	.023	.070	.560	270
12	1	Blue	19/25	.026	.070	.560	270
10	2	Black, White	19/23	.031	.070	.560	270
12	4	Black, White, Brown, Red	19/25	.026	.070	.510	250
12	6	Black, White, Brown, Green, Red, Yellow	19/25	.026	.070	.560	320
12	6	Blue, Brown, Green, Red, Yellow, Black	19/25	.026	.070	.600	350
10	1	White	19/23	.031	.070	.600	350
12	4	Yellow, Black, Brown, Green	65/30	.026	.070	.710	420
10	2	Blue, Red	105/30	.031	.070	.710	420
8	1	White	168/30	.037	.070	.710	420

SAE J1128 Round Trailer Cable
Polyethylene (PVC)
-50 to 80 Celsius

