



Your Quality Source for Electrical Wire

**Type STO**

NO. OF COND	AWG SIZE	COND. STRAND	COND. STRAND AWG	NOM. INS. THICKNESS	NOMINAL O.D.	CURRENT AMPS	APPROX WEIGHT LB/ 1K FEET
2	18	16	30	0.030	0.350	10	56
3	18	16	30	0.030	0.365	10	72
4	18	16	30	0.030	0.395	7	85
2	16	26	30	0.030	0.375	13	76
3	16	26	30	0.030	0.395	13	90
4	16	26	30	0.030	0.425	10	107
2	14	41	30	0.045	0.505	18	120
3	14	41	30	0.045	0.535	18	156
4	14	41	30	0.045	0.575	14	184
2	12	65	30	0.045	0.570	25	165
3	12	65	30	0.045	0.600	25	208
4	12	65	30	0.045	0.650	20	254
2	10	104	30	0.045	0.620	30	195
3	10	104	30	0.045	0.655	30	262
4	10	104	30	0.045	0.705	25	323

UL Portable cable

600 Volts

-20 to 60 Celsius

Fully annealed stranded bare copper per ASTM B-174

Premium-grade, color-coded PVC

Jacket: Polyvinylchloride (PVC)

Applications: Portable tools, motors, floor maintenance equipment, hospital equipment, sound equipment, washing machines, portable lights, lamps and similar equipment.

Oil resistant jacket

Resists: oils, acids, alkalies, and ozone

