



Your Quality Source for Electrical Wire

**Type STW**

SIZE AWG	NO. OF CONDS.	NO. STRANDS	INSULATION THICKNESS	JACKET THICKNESS	NOMINAL O.D.	CURRENT AMPS	APPROX WEIGHT LB/ 1K FEET
<b>18</b>	2	16	.031	.062	.341	10	58.67
<b>18</b>	3	16	.031	.065	.365	10	64.47
<b>18</b>	4	16	.031	.068	.4	7	80
<b>16</b>	3	26	.03	.065	.395	13	80.21
<b>14</b>	3	41	.045	.085	.605	25	192.35
<b>12</b>	3	65	.048	.097	.605	25	192.35
<b>10</b>	3	104	.05	.095	.665	30	256.94
<b>10</b>	4	104	.05	.095	.748	25	337.18
<b>10</b>	3	104	.05	.095	.67	30	274.25
<b>8</b>	4	161	.06	.14	1.101	35	699
<b>6</b>	4	133	.065	.174	1.181	45	796.57

UL Portable cable

600 Volts

-34 to 105 Celsius

Bare copper conductors

Bare copper conductors; thermoplastic insulation; conductors twisted with polypropylene filler; thermoplastic jacket.

Power supply for portable garage lights, battery chargers, portable stage lights, and heavy duty power tools where subjected extra hard usage in dry or damp locations.

