



Your Quality Source for Electrical Wire

U.L AWM Style 3266

AWG	COND. STRANDING	NOM. INSUL. THICK. (IN)	NOM. O.D. (IN)	APPROX LBS/MFT
26	7/34	0.016	0.0500	2.00
24	7/32	0.016	0.0560	3.00
22	7/30	0.016	0.0610	4.00
20	7/28	0.016	0.0700	5.00
20	19/32	0.016	0.0690	5.00
18	7/26	0.016	0.0780	7.00
18	19/31	0.016	0.0790	7.00
16	19/29	0.016	0.0910	10.00
16	26/30	0.016	0.0920	11.00
14	19/27	0.016	0.1130	16.00
12	19/25	0.016	0.1390	27.00
10	37/26	0.016	0.1510	36.00
10	105/30	0.016	0.1580	38.00

UL 3266

Irradiated Cross-linked Polyethylene

Electronic Hook Up Wire

UL Recognized & CSA Certified

125°C, 300V

UL 3266 Description:

Conductor: Soft annealed, solid or stranded, tinned copper conductor

Insulation: Irradiated Cross-linked Polyethylene Insulation (XLPE)

Available Options: VW-1 Compound available. Prefused material available upon request

UL 3266 Applications:

UL 3266 Hook Up Wire may be used for internal wiring of appliances, computers, test equipment, business machines and other office and control equipment.

